



VersaPro™ 96% AFUE GASFURNACE MGM96EE*****NB



- ✓ Quiet Operation
- ✓ Superior Performance
- ✓ Durable Build & Finish
- ✓ Optional LP Kit
- ✓ Multi-Position Application
- ✓ 96% AFUE
- ✓ Two Stage
- ✓ Energy Efficient
- ✓ Compact Design

Upflow, and horizontal configurations compatible with R-410A products and does not include sensor to work with R-454B or R-32 refrigerant.

48 Remington Way
Hickory, KY 42051
270.366.0457

www.mrcool.com

Version Date: 01-03-2025



VersaPro™ 96% AFUE GAS FURNACE

MGM96EE**NB**

Facing even the most severe winter conditions, the MRCOOL® VersaPro™ 96% AFUE Gas Furnace delivers unparalleled performance with its quiet operation and high efficiency.

Its two-stage, consistent torque DC motor and 96% AFUE ensure significant savings on utility bills. Crafted with an aluminized steel tubular heat exchanger and stainless steel secondary heat exchanger, it guarantees durability and reliability.

Installation is hassle-free, fitting even in areas with limited space. Designed for multi-position installation in upflow or horizontal configurations, the furnace offers convenient left or right connections for gas or electric service. The inclusion of a removable bottom panel facilitates maintenance and installation, accommodating side or bottom return applications. Additionally, conversion to propane is straightforward with an optional LP kit.

The furnace's AHRI certification and ETL listing attest to its adherence to rigorous quality and performance standards. Registering the furnace within 90 days activates a 10-year parts warranty and a lifetime warranty on the heat exchanger, providing additional peace of mind. Even without registration, you're covered by a 5-year parts warranty and a 20-year heat exchanger warranty, ensuring enduring comfort and reliability.

SPECIFICATION

GAS FURNACE - 96% AFUE

UPFLOW HORIZONTAL	Unit	MGM96EE060B3NB	MGM96EE080B3NB	MGM96EE080C4NB	MGM96EE100C5NB	MGM96EE120D5NB	
Power Supply	V~Hz, Ph	120~60, 1	120~60, 1	120~60, 1	120~60, 1	120~60, 1	
Natural Gas	Input	Btu/h	60,000	80,000	80,000	100,000	120,000
	Output	Btu/h	57,000	76,000	76,000	95,000	115,000
Blower Size	inch	12.375 x 8	12.375 x 8	12.75 x 11.25	12.75 x 11.25	12.75 x 11.25	
Temp. Rise Range	°F	30-60	35-65	35-65	35-65	40-70	
Cabinet Size (WxDxH)	inch	17.52 x 28.74 x 33.74	17.52 x 28.74 x 33.74	20.98 x 28.74 x 33.74	20.98 x 28.74 x 33.74	24.49 x 28.74 x 33.74	
Packing Size (WxDxH)	inch	20 x 31.02 x 40.35	20 x 31.02 x 40.35	23.54 x 31.02 x 40.35	23.54 x 31.02 x 40.35	27.05 x 31.02 x 40.35	
Motor	HP	3/4	3/4	3/4	1	1	
Max CFM @ 0.5ESP	CFM	1280	1271	1312	2031	2127	
Motor Speeds		5 speed	5 speed	5 speed	5 speed	5 speed	
Gas Type		NG (LP w/kit)	NG (LP w/kit)	NG (LP w/kit)	NG (LP w/kit)	NG (LP w/kit)	
Gas Connection Size	inch	1/2	1/2	1/2	1/2	1/2	
Net Weight	lbs	131	139	142	153.5	169	
Gross Weight	lbs	162	168	185.5	191	210	



Data provided by AHRI